

MICRO SWITCH  
 250V AC 6A RESISTIVE LOAD  
 250V DC 0.5A RESISTIVE LOAD

COLOR : 10YR7.5/14  
 DETECTION TORQUE : About 10.0N · cm  
 REVOLUTION : 1RPM  
 AMBIENT TEMPERATURE : -10 ~ +40°C

	POWER SUPPLY	APPLICATION TYPE DESIGNATION
	AC100V	PRL-5-WP
	AC200V	PRL-5-VP

○ (Required length)

	ℓ	ℓ <sub>o</sub>	NOTE	Q'ty
	470 ~ 620	0 ~ 150		
	670 ~ 1020	0 ~ 350		
	770 ~ 1220	0 ~ 450		


○ (Required length)

FLAMEPROOF TYPE G 1/2" CABLE GLAND

※Please specify the cable gland type.

	CABLE GLAND TYPE	Range of acceptable cable size
	SXC-16B-1	φ 10 ~ φ 12
	SXC-16B-2	φ 8 ~ φ 10

○ (Required length)



APPROVAL No.: T66814  
 APPLICATION RANGE: d2G4  
 EXPLOSION-PROTECTED CONSTRUCTION: d  
 EXPLOSION CLASS: 2  
 IGNITABILITY: G4

Q'ty:

図曆 CHANGE NOTICE	承認 APPROVED	検図 CHECKED	製図 DRAWN ohno	名称 TITLE PRL-F7EB PADDLE TYPE LEVEL SWITCH
	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2.5	日付 DATE Mar, 3, 2016	図面番号 DRG. No. HR-91203
東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.				